PHOTOCATALYTIC FIBER AND ITS PRODUCTION

Patent number:

JP9000947

Publication date:

1997-01-07

Inventor:

TAKEMURA TORU; KAMO JUN; UENISHI MICHIHARU

Applicant:

MITSUBISHI RAYON CO

Classification: - international:

B01J21/06; B01J35/02; B01J35/06; D06M11/46; B01J21/00; B01J35/00; D06M11/00; (IPC1-7): B01J35/06; B01J21/06; B01J35/02; D06M11/46

- european:

Application number: JP19950176934 19950621 Priority number(s): JP19950176934 19950621

Report a data error here

Abstract of JP9000947

PURPOSE: To allow a photocatalytic fiber to exhibit photocatalytic action even in a place hardly exposed to light by carrying a photocatalyst on an optical fiber having a light leaking part and to enhance the efficiency of utilization of the photocatalyst. CONSTITUTION: An aq. dispersion of a photocatalyst is applied to the surface of an optical fiber and the photocatalyst is fixed. That is, photocatalyst powder is dispersed in a resin soln. prepd. by dissolving epoxy resin, acrylic resin or styrene resin in an org. solvent, a soln. of a silane coupling agent or water glass, the resultant liq. is applied to the surface of an optical fiber and the powder is fixed by polymn. curing or by evaporating the liq. by heating. The polymn. curing is carried out by a heating reaction or irradiation with active energy such as UV rays. A commercially available titanium dioxide or zirconium oxide sol may be used as the aq. dispersion. The objective photocatalytic fiber may be produced by applying a partial hydrolyzate of an organometallic compd. to the surface of an optical fiber and fixing it by condensation reaction.

Data supplied from the esp@cenet database - Worldwide